

VETROGARD Attack P7B

Attack resistant security glass



Sample configuration only - Non contractual picture

Classification



Attack

Attack resistant glazing intended to hold back forced entry for a specific time.

Technical Specifications

Resistance class

Impact resistance

Application conditions

ID-No.

Dimensional tolerances (width/height)

P7B, (EN 356)

1(B)1 (EN 12600)

For more information and assistance, please contact your local Vetrotech agent and refer to the relevant "Quality and Application Guidelines".

Always verify the side of attack.

SP722

≤1000 mm: -1 / +2 mm | ≤2000 mm: -1 / +2 mm | >2000 mm: -1 / +3 mm

Product / CE / DoP-Code

Nominal thickness

Maximum glass size

Thickness tolerance

Weight

Sound reduction R_w (EN 140-3)

Light transmission (EN 410)

Light reflection p_L ext./int. (EN 410)

U_g value, $W/m^2 \cdot K$ (EN 673)

g value (EN 410)

PLANICLEAR

22 mm

12.0 m² (2400 mm / 5000 mm)

± 1 mm

50 kg/m²

38dB

86%

8% / 8%

4.7

0.71

DIAMANT

22 mm

12.0 m² (2400 mm / 5000 mm)

± 1 mm

50 kg/m²

38dB

89%

8% / 8%

4.7

0.76

Additional Informations

DoP: Declaration of Performance - available upon request from your sales office.

NPD: No Performance Determined