

# VETROGARD Attack P6B

Attack resistant security glass



Sample configuration only - Non contractual picture

## Classification



### Attack

Attack resistant glazing intended to hold back forced entry for a specific time.

## Technical Specifications

### Resistance class

Impact resistance

Application conditions

ID-No.

Dimensional tolerances (width/height)

### P6B, (EN 356)

1(B)1 (EN 12600)

For more information and assistance, please contact your local Vetrotech agent and refer to the relevant "Quality and Application Guidelines".

Always verify the side of attack.

SP615

≤1000 mm: -1 / +2 mm | ≤2000 mm: -1 / +2 mm | >2000 mm: -1 / +3 mm

### Product / CE / DoP-Code

Nominal thickness

Maximum glass size

Thickness tolerance

Weight

Sound reduction  $R_w$  (EN 140-3)

Light transmission (EN 410)

Light reflection  $p_L$  ext./int. (EN 410)

$U_g$  value,  $W/m^2 \cdot K$  (EN 673)

$g$  value (EN 410)

### PLANICLEAR

15 mm

9.6 m<sup>2</sup> (2400 mm / 4000 mm)

± 1 mm

33 kg/m<sup>2</sup>

37dB

87%

8% / 8%

4.8

0.72

### DIAMANT

15 mm

9.6 m<sup>2</sup> (2400 mm / 4000 mm)

± 1 mm

33 kg/m<sup>2</sup>

37dB

89%

8% / 8%

4.8

0.77

### Additional Informations

DoP: Declaration of Performance - available upon request from your sales office.

NPD: No Performance Determined