

VETROGARD ATTACK P7B

Attack resistant security glass



Sample configuration only - Non contractual picture

Classification



Attack

Attack resistant glazing intended to hold back forced entry for a specific time.

Technical Specifications

Resistance class

Impact resistance

Application conditions

ID-No.

Dimensional tolerances (width/height)

P7B, glass attack (EN 356)

1(B)1 (EN 12600)

For more information and assistance, please contact your local Vetrotech agent and refer to the relevant "Quality and Application Guidelines".
Always verify the side of attack.

SP722

≤1000 mm: -1 / +2 mm | ≤2000 mm: -1 / +2 mm | >2000 mm: -1 / +3 mm

Product / CE / DoP-Code

Nominal thickness

Maximum glass size

Thickness tolerance

Weight

Sound reduction R_w (EN 140-3)

Light transmission (EN 410)

Light reflection p_L ext./int. (EN 410)

U_g value, $W/m^2 \cdot K$ (EN 673)

g value (EN 410)

PLANICLEAR

22 mm

12.0 m² (2400 mm / 5000 mm)

± 1 mm

50 kg/m²

38dB

84%

8% / 8%

4.7

0.67

DIAMANT

22 mm

12.0 m² (2400 mm / 5000 mm)

± 1 mm

50 kg/m²

38dB

86%

8% / 8%

4.7

0.72

Additional Informations

DoP: Declaration of Performance - available upon request from your sales office.

NPD: No Performance Determined