

# POLYGARD ATTACK P6B

Attack resistant security glass for interior application only



Sample configuration only - Non contractual picture

## Classification



**Attack**  
Attack resistant glazing intended to hold back forced entry for a specific time.

## Technical Specifications

### Resistance class

Impact resistance
Application conditions
ID-No.
Dimensional tolerances (width/height)

### P6B, glass attack (EN 356)

1(B)1 (EN 12600)
For more information and assistance, please contact your local Vetrotech agent and refer to the relevant “Quality and Application Guidelines”. Always verify the side of attack.
SP615
≤1000 mm: -1 / +2 mm   ≤2000 mm: -1 / +3 mm   >2000 mm: -1 / +4 mm

### Product / CE / DoP-Code

Nominal thickness
Maximum glass size
Thickness tolerance
Weight
Sound reduction Rw (EN 140-3)
Light transmission (EN 410)
Light reflection pL ext./int. (EN 410)
Ug value, W/m²·K (EN 673)
g value (EN 410)

### PLANICLEAR

15 mm
6.0 m² (2000 mm / 3000 mm)
± 2 mm
28 kg/m²
36dB
86%
8% / 8%
4.8
0.75

### DIAMANT

15 mm
6.0 m² (2000 mm / 3000 mm)
± 2 mm
28 kg/m²
36dB
87%
8% / 8%
4.8
0.78

### Additional Informations

DoP: Declaration of Performance - available upon request from your sales office.  
NPD: No Performance Determined