


VETROGARD® ATTACK P7B

Attack resistant security glass for interior application

CLASSIFICATION



Attack

Attack resistant glazing intended to hold back forced entry for a specific time.

AVAILABLE OPTIONS



+ Alarm



+ Coloring
+ Digital printing
+ Screen Printing
+ Shapes



+ Climate control
+ Dynamic privacy
+ Extra clear
+ Noise control



+ Double glazing
+ Solar control
+ Tinting

Contact us to personalize your solution
to meet your project requirements.

TECHNICAL SPECIFICATIONS*

Resistance Class

Impact resistance	1(B)1 (EN 12600)
Application conditions	See Quality Guideline, Application Instructions.
ID-No.	SP 722
Hazardous material contained	None
Dimensional tolerances (height/width)	≤1000mm: -1/+2mm ≤2000mm: -1/+2mm >2000mm: -1/+3mm

P7B (EN 356)

Product

Nominal thickness	22mm
Basic glass	Planilux India
Maximum glass size	Based on maximum manufacturing sizes; Please get in touch with Vetrotech representative for more information
Thickness tolerance	+1 / -1 mm
Weight	50 kg/m ²
Sound reduction Rw (EN 140-3)	NPD [#]
Light transmission (EN 410)	82%
Light reflection pL ext./int. (EN 410)	8% / 8%
U value (EN 673)	4.8 W/m ² K
g value (EN 410)	0.65
Energy transmission tE (EN 410)	56%

Vetrogard® Attack P7B

*Valid for products manufactured at the 'World Glass Complex' of Saint-Gobain India Pvt. Ltd. - Vetrotech Business

Shapes: dimensional tolerances may vary +1mm

[#]NPD: No Performance Declared