

VDS® HOLLOW METAL DOORS

20, 45, 60, 90, 180 Minute Fire-Rated Doors

CLASSIFICATION

PRODUCT DESCRIPTION



VDS HM Doors are available in traditional design configurations allowing for maximum hardware options and fire ratings. Non-Temp Rise HM doors are available for 20 and 45 minutes. Temperature rise available for 60-90 minutes.

TECHNICAL SPECIFICATIONS

US Testing	UL 10B, UL 10C, NFPA 80, 252, ASTM E119
Canadian	CAN/ULC-S104
Finish Options	Powder Coat/Enamel (Custom colors available. Surcharges may apply.)
Fabrication	Welded
Certification	Underwriters Laboratories - UL LLC
Fabricated in the US	Yes
Single/Double Doors	Yes
Weight (lbs/lin. ft; kg/lin. ft.)	5 (2.3) Weight per unit provided prior to shipment

MAXIMUM DIMENSIONS

Daylight opening size limitations dependent on maximum exposed glass area.

Maximum Height (in.; m)	96 (2.438) Call for details
Maximum Width (in.; m)	42 (1.067) Call for details

DETAILS



Rev. 1.116 The information published in this document is correct at the time of going to press. Such information may be subject to change and products may be modified.