

VDS® 120 FRAMING SYSTEM

Vetrotech Design Solutions Fire-Resistive Framing System

CLASSIFICATION



Fire-Resistive

This glass product can withstand fire exposure to the non-fire side and protects from flames, smoke, radiant heat and hot gases.



Fire-Rated System

This system solution brings together framing, doors and glazing for an all-in-one fire-rated barrier. Can be complemented with 90 minute doors.



Hose Stream Tested

This product has passed the hose stream test.

AVAILABLE OPTIONS



+ Protection



+ Finish Color



+ Sound Reduction
 + Interior/Exterior

Contact us for a personalized solution to meet your product requirements.

TECHNICAL SPECIFICATIONS

Fire rating

120 Minutes

USA/Canada Testing Standards

ASTM E119, UL 263, CAN/ULC-S101, LARR 26129
 Can be customized to meet up to Level 3, per US 752

Certification

Listed and Labeled with Underwriters Laboratories Inc. (UL file number R21527)

Application Conditions

Interior/Exterior

Product

VDS® 120

Finish Options

Enamel/Powder Coat (Custom colors available. Surcharges may apply.)

Fabrication

Knock Down/Welded (On special request)

Fabrication Location

USA (Auburn, Washington)

Weight (lbs/lin. ft., kg/lin. m)

6.7 (10) [Does not include glass]

Glazing Options

Contraflam 120, Contraflam Structure 120

Door Type

Single/Double Doors

