

VDS® LITE FRAMING SYSTEM

Vetrotech Design Solutions Fire-Protective Window System

CLASSIFICATION



Fire-Protective

This product can withstand fire exposure to the non-fire side and protects from flames, smoke, and hot gases.



Fire-Rated System

This system solution brings together framing, doors and glazing for an all-in-one fire-rated barrier. Can be complemented with 20/45/60/90 minute doors.



Hose Stream Tested

This product has passed the hose stream test.

AVAILABLE OPTIONS



+ Protection



+ Finish Color



+ Sound Reduction
 + Interior/Exterior

Contact us for a personalized solution to meet your product requirements.

TECHNICAL SPECIFICATIONS

Fire rating

20/45/60/90 Minutes

USA/Canada Testing Standards

NFPA 257, UL 9, CAN/ULC-S106, LARR 26129

Certification

Listed and Labeled with Underwriters Laboratories Inc. (UL file number R21527)

Application Conditions

Interior and Exterior

Product

VDS® Lite

Finish Options

Enamel/Powder Coat (Custom colors available. Surcharges may apply.)

Fabrication

Knock Down/Fully welded modules (On special request)

Fabrication Location

USA (Auburn, Washington)

Weight (lbs/lin. ft., kg/lin. m)

2 (3) [Does not include glass]

Glazing Options

Contraflam 45/60, Keralite Select Filmed or Laminated 20/45/60/90

Door Type

Single/Double Doors

