

POLYGARD ATTACK RC5 anti-panic

Attack resistant security glass for interior application only



Sample configuration only - Non contractual picture

Classification



Attack
Attack resistant glazing intended to hold back forced entry for a specific time.

Technical Specifications

Resistance class

Impact resistance
Application conditions
ID-No.
Dimensional tolerances (width/height)

RC5 anti-panic hand-hole, glass attack (EN 1627)

1(B)1 (EN 12600)
For more information and assistance, please contact your local Vetrotech agent and refer to the relevant “Quality and Application Guidelines”. Always verify the side of attack.
RC5.89 AP-hand hole opening of 90x90 mm
≤1000 mm: -1 / +3 mm ≤2000 mm: -1 / +4 mm >2000 mm: -1 / +5 mm

Product / CE / DoP-Code

Nominal thickness
Maximum glass size
Thickness tolerance
Weight
Sound reduction Rw (EN 140-3)
Light transmission (EN 410)
Light reflection pL ext./int. (EN 410)
Ug value, W/m²·K (EN 673)
g value (EN 410)

PLANICLEAR

89 mm
1.6 m² (1500 mm / 3000 mm)
± 3 mm
184 kg/m²
NPD
60%
6% / 6%
2.7
0.50

DIAMANT

89 mm
1.6 m² (1500 mm / 3000 mm)
± 3 mm
184 kg/m²
NPD
66%
6% / 6%
2.7
0.60

Additional Informations

DoP: Declaration of Performance - available upon request from your sales office.
NPD: No Performance Determined