

# POLYGARD ATTACK RC6

Attack resistant security glass for interior application only



Sample configuration only - Non contractual picture

## Classification



### Attack

Attack resistant glazing intended to hold back forced entry for a specific time.

## Technical Specifications

### Resistance class

Impact resistance

Application conditions

ID-No.

Dimensional tolerances (width/height)

### RC6, glass attack (EN 1627)

1(B)1 (EN 12600)

For more information and assistance, please contact your local Vetrotech agent and refer to the relevant "Quality and Application Guidelines".

Always verify the side of attack.

RC6.93

≤1000 mm: -1 / +3 mm | ≤2000 mm: -1 / +4 mm | >2000 mm: -1 / +5 mm

### Product / CE / DoP-Code

Nominal thickness

Maximum glass size

Thickness tolerance

Weight

Sound reduction  $R_w$  (EN 140-3)

Light transmission (EN 410)

Light reflection  $p_L$  ext./int. (EN 410)

$U_g$  value,  $W/m^2 \cdot K$  (EN 673)

$g$  value (EN 410)

### PLANICLEAR

93 mm

1.5 m<sup>2</sup> (1500 mm / 3000 mm)

± 4 mm

196 kg/m<sup>2</sup>

NPD

60%

6% / 6%

2.7

0.46

### DIAMANT

93 mm

1.5 m<sup>2</sup> (1500 mm / 3000 mm)

± 4 mm

196 kg/m<sup>2</sup>

NPD

67%

6% / 6%

2.7

0.55

### Additional Informations

DoP: Declaration of Performance - available upon request from your sales office.

NPD: No Performance Determined