

# VETROGARD® ATTACK P6B

Attack resistant security glass for interior application

## CLASSIFICATION



### Attack

Attack resistant glazing intended to hold back forced entry for a specific time.

## AVAILABLE OPTIONS



+ Alarm



+ Coloring  
+ Digital printing  
+ Screen Printing  
+ Shapes



+ Climate control  
+ Dynamic privacy  
+ Extra clear  
+ Noise control



+ Double glazing  
+ Solar control  
+ Tinting

Contact us to personalize your solution  
to meet your project requirements.

## TECHNICAL SPECIFICATIONS\*

### Resistance Class

Impact resistance	1(B)1 (EN 12600)
Application conditions	See Quality Guideline, Application Instructions.
ID-No.	SP 615
Hazardous material contained	None
Dimensional tolerances (height/width)	≤1000mm: -1/+2mm   ≤2000mm: -1/+2mm   >2000mm: -1/+3mm

### P6B (EN 356)

### Product

Nominal thickness	15mm
Basic glass	Planilux India
Maximum glass size	Based on maximum manufacturing sizes; Please get in touch with Vetrotech representative for more information
Thickness tolerance	+1 / -1 mm
Weight	33 kg/m <sup>2</sup>
Sound reduction Rw (EN 140-3)	NPD <sup>#</sup>
Light transmission (EN 410)	85%
Light reflection pL ext./int. (EN 410)	8% / 8%
U value (EN 673)	5.1 W/m <sup>2</sup> K
g value (EN 410)	0.71
Energy transmission tE (EN 410)	64%

### Vetrogard® Attack P6B

\*Valid for products manufactured at the 'World Glass Complex' of Saint-Gobain India Pvt. Ltd. - Vetrotech Business

Shapes: dimensional tolerances may vary +1mm

<sup>#</sup>NPD: No Performance Declared