

CONTRAFLAM® One 120 US/C IGU

Fire rated clear interlayerd, tempered safety glass for exterior applications

Classification



Fire resistive

This glass product can withstand fire exposure to the non-fire side and protects from flames, smoke, radiant heat and hot gases.



Impact safety from either surface

Impact safety rated to meet the highest human impact safety ratings.



Hose Stream tested

This product has passed a hose stream test

Available Options



→ Extra clear



→ Patterned glass

Contact us for a personalized solution to meet your product requirements.

Technical Specifications

HYBRIDCORE TECHNOLOGY™

Fire Rating

120 minutes

US / Canada Standards	UL 263; ASTM E-119; CAN/ULC S101; ASTM E2229
Building code Marking	W-120
Impact Safety Rating	ANSI Z97.1; CPSC 16CFR 1201-CAT II; CAN/CGSB - 12.1-M90
Application	Exterior

Product

CONTRAFLAM® One 120 IGU

Nominal thickness	2-5/32 in. (55 mm)
Thickness tolerance	+1/8" / -3/32" (+3/- 2 mm)
Weight	15,21 lb/sq. ft. (74 kg/m²)
Glass 1	1/4 in. (6 mm) PLANITHERM XN II (low-E coated tempered)
Spacer	1/4 in. (6 mm) Argon
Glass 2	CF120-1 IGU (37 mm)
STC/OITC rating (ASTM E 413/E1332)	41 / 35 calculated
Visible transmittance (NFRC 200)	78%
Light reflection pL ext./int. (CIE 15)	11% / 11%
U-factor (Btu/h*sq.ft*deg F) (NFRC 100)	Winter: 0.215 / Summer: 0.207
Solar heat gain coefficient (NFRC 200)	0.55
Energy transmission (NFRC 300)	44%
Door. Temp Rise: Max exposed w x h. a	126-3/16 in. (3206mm);
[Based on Intertek Spec ID 73711]	Area: 45.1 sq. ft. (4.19 m²)
Temperature range	-40°C / +60°C (-40°F / + 140 °F)

Additional Information to CONTRAFLAM 120-1

Values based on Planiclear base glass

Dimensions: please check CONTRAFLAM 120-1 mono datasheets