

VDS® 60 Framing System

Vetrotech Design Solutions Fire-Rated Framing System

Classification



Fire-Resistive

This glass product can withstand fire exposure to the non-fire side and protects from flames, smoke, radiant heat, and hot gases.



Fire-Rated System

This system solution brings together framing, doors, and glazing for an all-in-one fire-rated barrier. Complement with 60-minute doors.



Hose Stream Tested

This product has passed a hose stream test.

Available Options



→ Protection



→ Finish Color



→ Noise Reduction
→ Interior / Exterior

Contact us for a personalized solution to meet your product requirements.

Technical Specifications

Fire Rating

60 minutes

US / Canada Standards

ASTM E119, UL 263, CAN/ULC-S101, LARR 26129

Certification

Can be customized to meet up to Level 3, per UL 752

Application

Listed and Labeled with Underwriters Laboratories Inc. (UL File Number R21527)

Interior / Exterior

Product

VDS 60

Finish Options

Enamel / Powder Coat, custom colors available

Fabrication

Knock-Down standard, welded option available

Fabrication Location

Faribault, Minnesota, USA

Weight

4 lbs/lin. ft. (6 kg/lin. m) (does not include glass)

Glazing Options

CONTRAFLAM 60 and CONTRAFLAM Structure 60

Door Type

Single/Double Doors

Product characteristics are subject to change without notice and may vary depending on manufacturing size and composition. Available options are dependent on product type and application. Contact your Vetrotech representative for further support.