

VDS® Lite

Vetrotech Design Solutions Fire-Protective Window System

Classification



Fire-Protective

This glass product can withstand fire exposure to the non-fire side and protects from flames, smoke, and hot gases.



Fire-Rated System

This system solution brings together framing, doors, and glazing for an all-in-one fire-rated barrier. Complement with 45 / 60 / 90 minute doors.



Hose Stream Tested

This product has passed a hose stream test.

Available Options



→ Protection



→ Finish color



→ Noise reduction
→ Interior / Exterior

Contact us for a personalized solution to meet your product requirements.

Technical Specifications

Fire Rating

US / Canada Standards

Certification

Application

45 / 60 / 90 minutes

NFPA 257, UL 9, CAN/ULC-S106, LARR 26129

Listed and Labeled with Underwriters Laboratories Inc. (UL File Number R21257)

Interior / Exterior

Product

Finish Options

Fabrication

Fabrication Location

Weight

Glazing Options

Door Type

VDS Lite

Enamel / Powder coat, custom colors available

Knock-Down is standard, fully welded option available

Faribault, Minnesota, USA

2 lbs/lin. ft. (3 kg/lin. m) (does not include glass)

CONTRAFLAM 45 / 60, KERALITE V-NIX Filmed or Laminated 45 / 60 / 90, PYROSWISS 45

Single / Double doors

Product characteristics are subject to change without notice and may vary depending on manufacturing size and composition. Available options are dependent on product type and application. Contact your Vetrotech representative for further support.