



Photo by Salvatore Cozzo – Sic Ilcma

VETROFLAM CLIMAPLUS SCREEN

E 30 & EW 30

Fire resistant glass solution for facade application with integrated blinds



PERFORMANT PROTECTION

vetrotech.com



VETROFLAM CLIMAPLUS SCREEN* is a fire resistive facade solution, composed of a Vetrolam glass mounted into a double glazed unit with integrated blinds.

Product Benefits

The aesthetic VETROFLAM CLIMAPLUS SCREEN offers high visual and thermal comfort while preserving people lives and assets against fire.



Safety

- + E 30 and EW 30 fire resistance
- + Impact resistance according to EN 12600, 1(C)1



Design

- + Choice of colors
- + Manual and motorized control



Comfort

- + Thermal and acoustic comfort
- + UV and glare protection, daylight optimization
- + Day and night-time privacy
- + Cleanliness and anti-condensation



Sustainability

- + Energy savings
- + Natural daylight

Blinds control

Cord or external motor



Swipe system



Knob



Internal motor



Discover more about the Pellini Screenline range of blinds and controls:
www.pelliniscreenline.net

Performances

- Fire protection: E 30 and EW 30 - one fire direction outside to inside
- Light transmission**: up to 81%
- Solar control: $0,09 (90^\circ) < g^{**} < 0,64 (0^\circ)$
- Thermal performance: $Ug^{**} > 1.1 W/(m^2.K)$

**with blinds completely up

*Vetroflam Climaplus Screen is a CE marked solution.

Applications

- Openable and fix windows
- Partitions

Features

- Dimensions: up to 1056 × 1656 mm
- Spacer thickness: 27 mm and 24 mm
- Frame: Schüco AWS75 FR30
- Blinds: Pellini

For more information, please contact your Vetrotech advisor:
 Vetrotech Saint-Gobain UK
 Herald Way, Binley Industrial Estate
 Coventry, CV3 2ZG, UK
 Tel: +44 247 654 76 20 ; uk@vetrotech.com

