# POLYGARD Attack P6B

Attack resistant security glass for interior application only

*Sample configuration only - Non contractual picture*

## Classification

**Attack**

**Attack resistant glazing intended to hold back forced entry for a specific time.**

## Technical Specifications

| Resistance class | P6B, (EN 356) |
|---|---|
| Impact resistance | 1(B)1 (EN 12600) |
| Application conditions | For more information and assistance, please contact your local Vetrotech agent and refer to the relevant "Quality and Application Guidelines".<br>Always verify the side of attack. |
| ID-No. | SP615 |
| Dimensional tolerances (width/height) | ≤1000 mm: -1 / +2 mm \| ≤2000 mm: -1 / +3 mm \| >2000 mm: -1 / +4 mm |

| Product / CE / DoP-Code | PLANICLEAR | DIAMANT |
|---|---|---|
| Nominal thickness | 15 mm | 15 mm |
| Maximum glass size | 6.0 m² (2000 mm / 3000 mm) | 6.0 m² (2000 mm / 3000 mm) |
| Thickness tolerance | ± 2 mm | ± 2 mm |
| Weight | 28 kg/m² | 28 kg/m² |
| Sound reduction Rw (EN 140-3) | 37 dB | 37 dB |
| Light transmission (EN 410) | 86% | 87% |
| Light reflection pL ext./int. (EN 410) | 8% / 8% | 8% / 8% |
| Ug value, W/m²·K (EN 673) | 4.8 | 4.8 |
| g value (EN 410) | 0.75 | 0.78 |

***Additional Informations***

*DoP: Declaration of Performance - available upon request from your sales office.*

*NPD: No Performance Determined*

© Vetrotech Saint-Gobain | 07.2025 | EN

vetrotech SAINT-GOBAIN

VETROTECH SAINT-GOBAIN INTERNATIONAL AG
Industriestrasse 44 / 3175 Flamatt / Switzerland
Phone +41 31 336 81 81 / vetrotech.com