POLYGARD Attack P8B

Attack resistant security glass for interior application only

Sample configuration only - Non contractual picture

Classification

Attack

Attack resistant glazing intended to hold back forced entry for a specific time.

Technical Specifications

Resistance class	P8B, (EN 356)
Impact resistance	1(B)1 (EN 12600)
Application conditions	For more information and assistance, please contact your local Vetrotech agent and refer to the relevant "Quality and Application Guidelines". Always verify the side of attack.
ID-No.	SP817
Dimensional tolerances (width/height)	≤1000 mm: -1 / +2 mm | ≤2000 mm: -1 / +3 mm | >2000 mm: -1 / +4 mm

Product / CE / DoP-Code	PLANICLEAR	DIAMANT
Nominal thickness	17 mm	17 mm
Maximum glass size	6.0 m² (2000 mm / 3000 mm)	6.0 m² (2000 mm / 3000 mm)
Thickness tolerance	± 2 mm	± 2 mm
Weight	30 kg/m²	30 kg/m²
Sound reduction Rw (EN 140-3)	37dB	37dB
Light transmission (EN 410)	84%	85%
Light reflection pL ext./int. (EN 410)	8% / 8%	8% / 8%
Ug value, W/m²·K (EN 673)	4.5	4.5
g value (EN 410)	0.74	0.76

Additional Informations

DoP: Declaration of Performance - available upon request from your sales office.

NPD: No Performance Determined

© Vetrotech Saint-Gobain | 07.2025 | EN

vetrotech SAINT-GOBAIN

VETROTECH SAINT-GOBAIN INTERNATIONAL AG
Industriestrasse 44 / 3175 Flamatt / Switzerland
Phone +41 31 336 81 81 / vetrotech.com