POLYGARD Attack RC3 anti-panic

Attack resistant security glass for interior application only

Sample configuration only - Non contractual picture

Classification

Attack

Attack resistant glazing intended to hold back forced entry for a specific time.

Technical Specifications

Resistance class	RC3 anti-panic, glass attack (EN 1627)
Impact resistance	1(B)1 (EN 12600)
Application conditions	For more information and assistance, please contact your local Vetrotech agent and refer to the relevant "Quality and Application Guidelines". Always verify the side of attack.
ID-No.	RC3 AP12
Dimensional tolerances (width/height)	≤1000 mm: -1 / +2 mm | ≤2000 mm: -1 / +3 mm | >2000 mm: -1 / +4 mm

Product / CE / DoP-Code	PLANICLEAR	DIAMANT
Nominal thickness	26 mm	26 mm
Maximum glass size	4.5 m² (1500 mm / 3000 mm)	4.5 m² (1500 mm / 3000 mm)
Thickness tolerance	± 2 mm	± 2 mm
Weight	46 kg/m²	46 kg/m²
Sound reduction Rw (EN 140-3)	NPD	NPD
Light transmission (EN 410)	78%	80%
Light reflection pL ext./int. (EN 410)	7% / 7%	7% / 7%
Ug value, W/m²·K (EN 673)	4.0	4.0
g value (EN 410)	0.69	0.73

© Vetrotech Saint-Gobain | 07.2025 | EN

Additional Informations

DoP: Declaration of Performance - available upon request from your sales office.

NPD: No Performance Determined

vetrotech SAINT-GOBAIN

VETROTECH SAINT-GOBAIN INTERNATIONAL AG
Industriestrasse 44 / 3175 Flamatt / Switzerland
Phone +41 31 336 81 81 / vetrotech.com