VETROGARD Attack P8B

Attack resistant security glass

Sample configuration only - Non contractual picture

Classification

Attack

Attack resistant glazing intended to hold back forced entry for a specific time.

Technical Specifications

Resistance class	P8B, (EN 356)
Impact resistance	1(B)1 (EN 12600)
Application conditions	For more information and assistance, please contact your local Vetrotech agent and refer to the relevant "Quality and Application Guidelines". Always verify the side of attack.
ID-No.	SP827
Dimensional tolerances (width/height)	≤1000 mm: -1 / +2 mm | ≤2000 mm: -1 / +3 mm | >2000 mm: -1 / +4 mm

Product / CE / DoP-Code	PLANICLEAR
Nominal thickness	27 mm
Maximum glass size	12.0 m² (2400 mm / 5000 mm)
Thickness tolerance	± 2 mm
Weight	58 kg/m²
Sound reduction Rw (EN 140-3)	39dB
Light transmission (EN 410)	85%
Light reflection pL ext./int. (EN 410)	8% / 8%
Ug value, W/m²·K (EN 673)	4.5
g value (EN 410)	0.69

Additional Informations

DoP: Declaration of Performance - available upon request from your sales office.

NPD: No Performance Determined

© Vetrotech Saint-Gobain | 07.2025 | EN

vetrotech SAINT-GOBAIN

VETROTECH SAINT-GOBAIN INTERNATIONAL AG
Industriestrasse 44 / 3175 Flamatt / Switzerland
Phone +41 31 336 81 81 / vetrotech.com