VETROGARD Bullet BR2-S

Bullet resistant security glass

Sample configuration only - Non contractual picture

Classification

Bullet

Bullet resistant glazing offering an effective resistance against specific weapons and ammunition types. A distinction is made between splintering (S) and non-splintering glass (NS).

Technical Specifications

Resistance class	BR2-S (with splinters, EN 1063)
Impact resistance	1(B)1 (EN 12600)
Application conditions	For more information and assistance, please contact your local Vetrotech agent and refer to the relevant "Quality and Application Guidelines".
Certificate of constancy of performance	AVCP System 1
ID-No.	226-S (old ID-No: HN 226-S)
Dimensional tolerances (width/height)	≤1000 mm: -1 / +2 mm | ≤2000 mm: -1 / +3 mm | >2000 mm: -1 / +4 mm

Product / CE / DoP-Code	PLANICLEAR	DIAMANT
Nominal thickness	26 mm	26 mm
Maximum glass size	12 m² (2400 mm / 5000 mm)	12 m² (2400 mm / 5000 mm)
Thickness tolerance	± 2 mm	± 2 mm
Weight	62 kg/m²	62 kg/m²
Sound reduction Rw (EN 140-3)	39 dB	39 dB
Light transmission (EN 410)	85%	88%
Light reflection pL ext./int. (EN 410)	8% / 8%	8% / 8%
Ug value, W/m²·K (EN 673)	5.0	5.0
g value (EN 410)	0.70	0.78

© Vetrotech Saint-Gobain | 07.2025 | EN

Additional Informations

DoP: Declaration of Performance - available upon request from your sales office.

NPD: No Performance Determined

vetrotech SAINT-GOBAIN

VETROTECH SAINT-GOBAIN INTERNATIONAL AG
Industriestrasse 44 / 3175 Flamatt / Switzerland
Phone +41 31 336 81 81 / vetrotech.com