VETROGARD Bullet BR6-NS SG2-NS P8B

Attack and bullet resistant security glass

Sample configuration only - Non contractual picture

Classification

Attack
Attack resistant glazing intended to hold back forced entry for a specific time.

Bullet
Bullet resistant glazing offering an effective resistance against specific weapons and ammunition types. A distinction is made between splintering (S) and non-splintering glass (NS).

Technical Specifications

Resistance class	BR6-NS SG2-NS (no splinters, EN 1063)
Resistance class	P8B (EN 356)
Impact resistance	1(B)1 (EN 12600)
Application conditions	For more information and assistance, please contact your local Vetrotech agent and refer to the relevant "Quality and Application Guidelines". Always verify the side of attack.
Certificate of constancy of performance	AVCP System 1
ID-No.	862.73-NS
Dimensional tolerances (width/height)	≤1000 mm: -1 / +3 mm | ≤2000 mm: -1 / +4 mm | >2000 mm: -1 / +5 mm

Product / CE / DoP-Code	PLANICLEAR	DIAMANT
Nominal thickness	73 mm	73 mm
Maximum glass size	8.5 m² (2200 mm / 4000 mm)	8.5 m² (2200 mm / 4000 mm)
Thickness tolerance	± 3 mm	± 3 mm
Weight	175 kg/m²	175 kg/m²
Sound reduction Rw (EN 140-3)	50 dB	50 dB
Light transmission (EN 410)	74%	83%
Light reflection pL ext./int. (EN 410)	7% / 7%	8% / 8%
Ug value, W/m²·K (EN 673)	3.8	3.8
g value (EN 410)	0.54	0.66

Additional Informations
DoP: Declaration of Performance - available upon request from your sales office.
NPD: No Performance Determined

© Vetrotech Saint-Gobain | 07.2025 | EN

vetrotech SAINT-GOBAIN

VETROTECH SAINT-GOBAIN INTERNATIONAL AG
Industriestrasse 44 / 3175 Flamatt / Switzerland
Phone +41 31 336 81 81 / vetrotech.com