VETROGARD Bullet AK47-NS Climaplus

Bullet resistant security glass for exterior application

Sample configuration only - Non contractual picture

Classification

Bullet

Bullet resistant glazing offering an effective resistance against specific weapons and ammunition types. A distinction is made between splintering (S) and non-splintering glass (NS).

Technical Specifications

Resistance class	AK47-NS (7.62x39 FMJ/PB/FeC (PS BALL))
Impact resistance	1(B)1 (EN 12600)
Application conditions	For more information and assistance, please contact your local Vetrotech agent and refer to the relevant "Quality and Application Guidelines". Always verify the side of attack.
Certificate of constancy of performance	VPAM Level 6 (VPAM-PM 2007)
ID-No.	CP AK47-NS
Dimensional tolerances (width/height)	≤1000 mm: -1 / +4 mm | ≤2000 mm: -1 / +5 mm | >2000 mm: -1 / +6 mm

Product / CE / DoP-Code	PLANICLEAR	DIAMANT
Nominal thickness	58 mm	58 mm
Maximum glass size	2.0 m² (2200 mm / 4000 mm) 8.8 m² with 14 mm spacer	2.0 m² (2200 mm / 4000 mm) 8.8 m² with 14 mm spacer
Spacer for DGU	10 mm	10 mm
Thickness tolerance	± 3 mm	± 3 mm
Weight	115 kg/m²	115 kg/m²
Sound reduction Rw (EN 140-3)	45 dB	45 dB
Light transmission (EN 410)	72%	78%
Light reflection pL ext./int. (EN 410)	10% / 11%	11% / 11%
Ug value, W/m²·K (EN 673)	1.3	1.3
g value (EN 410)	0.47	0.55

Additional Informations

DoP: Declaration of Performance - available upon request from your sales office.

NPD: No Performance Determined

© Vetrotech Saint-Gobain | 07.2025 | EN

vetrotech SAINT-GOBAIN

VETROTECH SAINT-GOBAIN INTERNATIONAL AG
Industriestrasse 44 / 3175 Flamatt / Switzerland
Phone +41 31 336 81 81 / vetrotech.com