

VDS® LITE DOORS

Vetrotech Design Solutions Fire-Protective Door System

CLASSIFICATION



Fire-Protective

This product can withstand fire exposure to the non-fire side and protects from flames, smoke, and hot gases.



Temperature Rise

Only applicable to fully glazed doors with Contraflam 60 or 90 installed.



Fire-Rated System

This system solution brings together framing, doors and glazing for an all-in-one fire-rated barrier.



Hose Stream Tested

This product has passed the required hose stream test.

AVAILABLE OPTIONS



+ Smoke Door



+ Finish Color
 + Hardware
 + Split Lite Door
 + Full Lite Door



+ Sound Reduction
 + Interior/Exterior

Approved installation in VDS Curtain Wall, VDS and VDS Lite framing systems.

Contact us for a personalized solution to meet your product requirements.

TECHNICAL SPECIFICATIONS

Fire rating

20/45/60/90 Minutes

USA/Canada Testing Standards

NFPA 80/252, UL 10B/10C, ANSI/UL 1784, CAN/ULC-S104, LARR 26129

Certification

Listed and labeled with UL Solutions (UL File Number R25396)

Application Conditions

Interior/Exterior

Product

VDS® Lite Doors

Finish Options

Enamel/Powder Coat (Custom colors available. Surcharges may apply.)

Fabrication

Welded

Fabrication Location

USA (Auburn, Washington)

Weight (lbs./lin. ft., kg./lin. m)

2 (3) [Does not include glass. Weight per unit provided prior to shipment]

Glazing Options

Keralite Select Filmed/Laminated 20/45/60/90, Contraflam 45/60/90, Pyroswiss 20/45

Door Type

Single/Double Doors

Door Leaf Maximum Dimensions (W x H in.)

Single: 42 in. x 96 in.
 Double: 84 in. x 96 in.

