

VDS® DOORS

Vetrotech Design Solutions Fire-Resistive Door System

CLASSIFICATION



Fire-Resistive

This glass product can withstand fire exposure to the non-fire side and protects from flames, smoke, radiant heat and hot gases.



Temperature Rise

Only applicable to fully glazed doors with Contraflam 60 or 90 installed.



Fire-Rated System

This system solution brings together framing, doors and glazing for an all-in-one fire-rated barrier.



Hose Stream Tested

This product has passed the hose stream test.

TECHNICAL SPECIFICATIONS

Fire rating

45/60/90 Minutes

USA/Canada Testing Standards

NFPA 80/252, UL 10B/10C, UL 1784, CAN/ULC-S104, LARR 26129

Certification

Listed and labeled with UL Solution (UL File Number R25396)

Application Conditions

Interior/Exterior

Product

VDS® Doors

Finish Options

Enamel/Powder Coat (Custom colors available. Surcharges may apply.)

Fabrication

Welded

Fabrication Location

USA (Auburn, Washington)

Weight (Lbs./lin. ft; kg/lin. m)

5-7 (7.4-10.4) [Does not include glass. Weight per unit provided prior to shipment.]

Glazing Options

Contraflam 45/60/90

Door Type

Single/Double Doors

Door Leaf Maximum Dimensions (W x H in.)

Single Door	60min	57 in. x 121 1/2 in.
Double Doors	60min	114 in. x 121 1/2 in.
Single Door	90min	48 in. x 96 in. OR 42 1/2 in. x 99 1/2 in.
Double Doors	90min	96 in. x 96 in. OR 86 7/16 in. x 99 1/4 in.

AVAILABLE OPTIONS



+ Protection



+ Finish Color
+ Hardware
+ Split Lite Door
+ Full Lite Door
+ Oversized Door



+ Sound Reduction
+ Interior/Exterior

Approved installation in VDS Curtain Wall and VDS framing systems.

Contact us for a personalized solution to meet your product requirements.