

VDS® Doors HI

60, 90 Minute Door Assemblies

CLASSIFICATION



PRODUCT FEATURES



PRODUCT DESCRIPTION

VDS® fire rated doors provide maximum vision area while maintaining narrow stiles and rails and complement our fully insulated VDS framing systems. Available for HVHZ applications as Vetrotech HI or as exterior system with UL listing and FBC approval.

TECHNICAL SPECIFICATIONS

Testing Standards/Conformity	UL 10B, UL 10C	NFPA 80, 252
	ASTM E-119	CAN/ULC-S104
Finish Options	Powder Coat, Enamel, Kynar	
Design Pressure (PSF)	+65/-65	
Fabrication	Welded, Select Hardware Options	
Certification	Underwriters Laboratories - UL	
Fabricated in the U.S.A.	Yes	
Testing Standards/Conformity	Yes	
Weight (lbs./lin.ft; kg/lin.ft)	5-7 (2.3-3.2) Weight per unit provided prior to shipment*	

MAXIMUM DIMENSIONS D.L.O. size limitations depend on maximum exposed glass area*

Maximum Height (in.;m)	120 (3.048) call for details
Maximum Width (in.;m)	57 (1.448) call for details

APPLICATION/GLAZING OPTIONS

- | | | |
|---|--|--|
| <input checked="" type="checkbox"/> Contraflam® | <input type="checkbox"/> Keralite® | <input type="checkbox"/> Pyroswiss® 20 |
| <input type="checkbox"/> Contraflam® Structure | <input checked="" type="checkbox"/> Contraflam® HI | <input checked="" type="checkbox"/> Exterior or HVHZ |