

CONTRAFLAM STRUCTURE 30 VETROGARD RC3 Climalit

Fire resistant safety glass for interior application

CLASSIFICATION



EI = Insulation

Ability to withstand fire exposure without transmission of fire to the non-fire side as a result of the passage of flames, hot gases or significant conduction of heat, thereby causing ignition of the non-fire exposed surface or materials in contact, and provides a barrier to heat to protect people.



Attack

Attack resistant glazing intended to hold back forced entry for a specific time.

AVAILABLE FEATURES



+ Protection



+ Matt finished
+ Screen printing
+ Shapes



+ Climate control
+ Extra clear
+ Noise control



+ Solar control
+ Tinting

Contact us to personalize your solution to meet your project requirements.

TECHNICAL SPECIFICATIONS

Fire resistance	EI 30 (EN 13501-2)
Resistance class	RC3 (EN 1627)
Reaction to fire	C-s1,d2 (EN13501-1)
Impact resistance	1(B)1 (EN 12600)
UV stability	Yes (EN ISO 12543-4), no formation of bubbles or yellowing after 2000 hours of exposure to radiation.
Application conditions	Restricted to interior applications. See Quality Guideline, Application Instructions.
Certificate of constancy of performance	0336-CPR-5064D - AVCP System 1
Hazardous material contained	None
Assembly	According to the installation guideline

Product / CE / DoP-Code	ZY014997
Nominal thickness	60 mm
Maximum glass size	1500 x 3000 mm
Thickness tolerance	+3 / -3 mm
Length tolerance	+4 / -4 mm
Weight	102.2 kg/m ²
Spacer	15 mm
Sound reduction Rw (EN 140-3)	45 (-3, -10) dB
Light transmission (EN 410)	72%
Light reflection pL (exterior/interior)	15% / 14%
U value, W/m ² K (EN 673)	2.3
g value	0.61
Energy transmission tE	44%

DoP: Declaration of Performances - you can request a DoP from your sales office